



M/V Seagard

Finnish flag, built by Sietas, Hamburg, DE , 1999
 LRS+100A1, Finnish ice class 1A Super, Call sign OJIW,
 IMO no. 9198977

Principal dimensions

Length over all	153.45 m
Breadth moulded	20.60 m
Trailer draught	6.40 m
Draught summer	7.00 m

Tonnage

DWT on 7.072 m draught	7 226 t
GT London rules 1969	10 488 t
NT London rules 1969	3 147 t

Tank capacities

HFO	945 t
MGO	132 t
Water ballast	3 979 t

Ro-Ro capacity

	Area	Lane meter	Max load
Weather deck	2 046 m ²	690 m	2.5 t/m ²
Main deck	1 852 m ²	611 m	5 t/m ²
Lower hold (excl. ramp)	929 m ²	305 m	8 t/m ²
Total	4 827 m²	1 609 m	

	Volume	Deck Height
Weather deck (under accommodation)		4.60 m
Main deck (bale)	9 335 m ³	5.00 m*
Lower hold (bale)	4 929 m ³	4.60 m

*(except under ramp)

Reefer plugs

25 pcs on weather deck
 25 pcs on weather deck

Ramps

2 x stern ramps
 Length 12 m
 Width 12.75 m and 4.1 m
 Lower hold fixed ramp
 Weather deck fixed ramp

Accommodation for drivers

Accommodation for 12 drivers in 6 cabins

Machinery

1 x Wärtsilä Vasa, 14V46B, 15.600 kW
 Scrubber, Croll Reynolds

Speed and consumption per day

Full draft 21.0 kn on abt 65 t
 Trailer draft 23.0 kn on abt 65 t
 Trailer draft 19.0 kn on abt 35 t

